



Technical parameters			
1	Nominal heat output	kW	10
2	Nominal heat output on the water side	kW	
3	Pressure required	Pa	12
4	Average efficiency	%	80,1
5	Average flue gas temperature	°C	247
6	Wood consumption	kg/h	3,2
7	Consumption of combustion air	m ³ /hour	30
8	Emission of CO to 13% O ₂	%	0,1
9	Flue gas mass flow	g/s	10,1
10	Weight	kg	195
11	Required min. cross section for circulating air - INPUT	cm ²	300
12	Required min. cross section for circulating air - OUTPUT	cm ²	500
13	Three-component insulated chimney - active height 5m	Ø cm	180
14	character of building construction with fireplace insert	warm air convection	yes
		heat storage without conv.	yes

Optional accessories

Cover frame (KR)
 Double glass (DS)
 Black printed glass (SM)
 Double SM glass (DSM)
 External ashtray (VOP)
 Segmental lining (SO)
 Lower hearth (ZO)
 Convection cover (DP)

Sizes			CHOPOK 670/440	CHOPOK 670/500	CHOPOK 670/560
1	A	mm	670		
2	F	mm	1150	1210	1270
3	C	mm	505		
4	DN	Ø mm	180		
5	B	mm	440	500	560
6	FF	mm			
7	R	mm			
8	AA	mm			
9	H	mm			
10	J	mm	325 + /160/		
11	K	Ø mm	4x125		
12	L	Ø mm	100		
13	M	mm			
14	N	mm	50		

